

TASKalfa 300i

MONOCHROME A3 MULTIFUNCTIONAL

► print ► copy ► scan ► fax

YOUR MULTITALENTED WORKGROUP SPECIALIST

Easy to integrate in any office workflow, the multitasking TASKalfa 300i performs as a copier, network printer, full-colour scanner and, optionally, as a fax. Its ample performance of 30 pages per minute combined with a document processor that scans at up to 50 images per minute ensures that this multifunctional gets every job done quickly.

- Up to 30/15 pages per minute A4/A3 in monochrome
- 2 GB RAM + 160 GB HD memory and storage
- Network printing, colour scanning and double-sided printing as standard
- Expandable dual fax ports and Internet fax
- Individual paper-handling and finishing options
- Enhanced security functions
- Long-life components provide exceptional efficiency and reliability



The full-colour, touch-screen control panel provides fast access to all functions.



The built-in multi-purpose tray with a paper capacity of up to 200 sheets can be used as a space-saving paper feeder handling paper weights up to 200gsm.



TASKalfa 300i MONOCHROME A3 MULTIFUNCTIONAL



The TASKalfa 300i incorporates extremely durable components that guarantee efficient and reliable operation to meet the demanding requirements of busy office environments. The TASKalfa 300i provides effective productivity and maximum flexibility whilst ensuring minimal impact on the environment.

General

Technology

KYOCERA Laser, mono component

Engine speed

Up to 30/15 pages per minute A4/A3

Resolution

600 x 600 dpi

Warm-up time

Approx. 29 seconds or less from power on

Time to first page

Approx. 5.1 seconds or less

Dimensions (W x D x H)

Main unit: 570 mm x 630 mm x 767.2 mm

Weight: Main unit: approx. 75 kg

Power source: AC 220 V ~ 240 V, 50/60 Hz

Power consumption

Printing: 610 W

Stand-by: 130 W

Sleep mode: 12 W

Noise (ISO 7779 / ISO 9296)

Printing: 66.5 dB(A)

Stand-by: 47 dB(A)

Safety standards

GS, TÜV, CE

This unit is manufactured according to ISO 9001 quality standard and ISO 14001 environmental standard. RoHS compatible.

Paper handling

All paper capacities quoted are based on paper thickness of max. 0.11 mm. Please use paper recommended by KYOCERA under normal environmental conditions.

Input capacity

Max. 200-sheet multi-purpose tray, 45–200 gsm, A3–A6R;

Max. 2 x 500 sheet universal paper cassette, 60–120 gsm, A3–A5R;

Max. input capacity with options: 2,200 sheets A4

Duplex unit

Duplex as standard, supports A3–A5R, 60–80 gsm

Output capacity

250 sheets face-down

Print functions

CPU: Power PC 750 FL @ 600 MHz

Memory: 2 Mg RAM + 160 GB HDD

Standard interface

USB 2.0 (Hi-Speed), Fast Ethernet 10/100Base-TX, CF slot

Controller language: PRESCRIBE

Emulations: PCL6, KPDL 3 (PostScript 3 compatible), XPS Direct Print, PDF Direct Print

Operating systems

All current Windows operating systems, Mac OS X Version 10.2 or higher, UNIX LINUX, as well as other operating systems on request

Fonts / barcodes

93 outline fonts (PCL6), 8 fonts (Windows Vista), 136 PostScript KPDL 3 fonts, 45 types of one-dimensional barcodes plus two-dimensional barcode (PDF-417) Downloadable fonts: KYOCERA, PCL + TrueType format, Type 1 + 3 format

Print features

Quick copy, proof and hold, private print, job storage and job management functionality

Copy functions

Max. original size: A3

Continuous copying: 1–999

Memory capacity: 2 GB RAM + 160 GB HDD

Zoom range: 25–400% in 1% steps

Preset magnification ratios: 5R / 5E

Digital features

Scan-once-copy-many, electronic sort, 2-in-1 and 4-in-1 function, image repeat copy, page numbering, cover mode, booklet copy, 160 GB document box, interrupt copy, form overlay

Exposure mode: Auto, manual: 7 or 13 steps

Image adjustments: Text + photo, text, photo

Scan functions

Functionality

Scan-to-email, scan-to-FTP (FTP via SSL), network TWAIN, scan-to-SMB, scan-to-box, scan-to-USB

Scan speed

50 (monochrome), 15 (colour) image per minute (A4, 300 dpi)

Scan resolution

600 dpi, 400 dpi, 300 dpi, 200 dpi, 200 x 100 dpi, 200 x 400 dpi, (256 greyscales)

Max. scan size: A3

Original recognition: Text, photo, text + photo, OCR

Interface: 10/100 Base-TX

Network protocol: TCP/IP

File types: PDF (high compressive/encrypted), JPEG, TIFF, XPS

Fax functions (optional)

Compatibility: ITU-T Super G3

Modem speed: Max. 33.6 kbps

Transmission speed: Max. 3 seconds (JBIG)

Scanning density

Normal: 8 dot/mm x 3.85 line/mm

Fine: 8 dot/mm x 7.7 line/mm

Superfine: 8 dot/mm x 15.4 line/mm

Ultrafine: 16 dot/mm x 15.4 line/mm halftone

Max. original size: A3

Compression method: JBIG, MMR, MR, MH

Memory: Standard 12 MB, max. 120 MB

Features

Opt. Internet fax, network faxing, rotate transmission, rotate reception, duplex fax reception, memory reception, mailbox, remote diagnostics, dual fax with second fax system

Consumables

TK-685 Toner-Kit

Microfine toner for 20,000 pages with 6% coverage

Options

Fax system (S) C

Internet Fax Kit (A)

Paper handling

DP-670(B) Reversing document processor

Max. 75 sheets, 45–160 gsm, A3–A5R, folio

PF-680 Paper feeder

Max. 2 x 500 sheets, 60–120 gsm, A3–A5R, folio

DF-780(B)* Document finisher + AK-670

Max. 1,000 sheets A4, A3–B5E, 64–128 gsm, 3 positions

stapling up to 50 sheets A4 or 25 sheets A3

DF-670(B) Internal document finisher

Max. 500 sheets A4, A3–A5R, 60–105 gsm, 1 position stapling up to 30 sheets A4 or 20 sheets A3

JS-670(B) Job separator

100-sheet internal job separator, 45–160 gsm, A3–A5R

*Adapter Kit AK-670 is required for the use of DF-780(B).

Memory

CompactFlash® card

1 slot (up to 4 GB) for printing forms, fonts, logos, macro storage

Fax memory

MM-16-128: Image memory (120 MB)

Security

Data Security Kit (E)

ISO 15408 (Common Criteria) with security level EAL3

Printed Document Guard Kit (A)

Optional interface

PS159: Wireless LAN (802.11b/g)

PS1109 Gigabit Ethernet

10BaseT / 100BaseTX / 1000BaseT (RJ-45)

PS1129 Fibre Optic: 100BaseSX (SC)

PS1129 Gigabit Fibre Optic: 1000BaseSX (SC)

Others

Platen cover (E)

CB-680: Wooden cabinet



Your KYOCERA Business Partner:

Kyocera Mita (UK) Ltd, 8 Beacontree Plaza, Gillette Way, Reading, RG2 0BS
Tel: 0118 931 1500, Fax: 0118 931 1108,
www.kyoceramita.co.uk, info@kyoceramita.co.uk

* Kyocera does not warrant that any specification mentioned will be error-free. Specifications are subject to change without notice. Information is correct at time of going to press. All other brand and product names may be registered trademarks and their respective holders are hereby acknowledged.



Product depicted includes optional extras.

KYOCERA